



Unmanned Vehicles

The **SEAHORSE-Class Autonomous Underwater Vehicle (AUV)** is an untethered, unmanned, underwater robotic vehicle, capable of preprogrammed independent operations from a host platform or shore facility. The AUV is currently powered with alkaline batteries and can operate for 72 hours at 4 knots for a nominal range of 300 nautical miles before requiring battery replenishment. Typical littoral zone AUV area characterization surveys can be conducted at operational depths of 30 to 300 meters.

The SEAHORSE AUV was designed to collect high-quality, precision-located environmental data in the littoral regions of the world. The driving design considerations were reliability, ease of maintenance and cost effectiveness. Operational factors of major concern were portability to worldwide survey locations, operations from T-AGS 60 class oceanographic vessels as well as other vessels of opportunity or shore-side facilities, ability to conduct a variety of preprogrammed search and survey patterns and reconfigurability to accommodate additional sensors or new requirements.

Seahorse I Characteristics

Diameter	38 inches
Length	27 feet, 10 inches
Displacement	10,000 pounds
Range	Minimum 300 nautical miles at 4 knots
Payload Volume	10 cubic feet, approximately
Power Source (initial)	9216 alkaline batteries
Launch and Recovery	Tilting slide bed launch and recovery system
Fixed Buoyancy	18.8 lbf/ft ³ Divinycell HCP70 structural foam
Trim Control	Fore and aft toroidal variable SW ballast tanks
Communications	RF (freewave and 80211B), limited acoustics
Control	3 CPUs: vehicle and mission controllers, ERG Prototype intelligent Controller architecture
Control Surfaces	4-fin "X" stern, MK50 electrical actuators
Drive Motor	5 HP Lynx Motion synchronous electric motor, Advanced Digital System 3-phase inverter
Propulsor	Ducted pumpjet, 3 rotor blades, nominal 255 RPM, cavitation-free at all depths

Seahorse II Instrumentation

Side-Scan Sonar	Benthos SIS-1500 AUV; 200-kHz Chirp
Multibeam (2005)	Kongsberg Simrad EM3000D; 300 kHz
CTD	Sea-Bird SBE-37
Pressure	Paroscientific Precision Pressure Sensor
INS aided	Kearfott KN 5053 SEANAV Ring Laser Gyro
GPS	Trimble TASMIN GPS Receiver
ADCP	RDI Acoustic Doppler Current Profiler
Modem	LinkQuest UWM3000
Acoustics	Edgetech Acoustic Transponders
Tracking	Paradigm System (WHOI)

The inclusion of any specific commercial product, commodity or service in this publication is for informational purposes only and does not imply endorsement by the Navy or NAVOCEANO.

